

TECHNICAL CHARACTERISTICS

SELENIA WR FORWARD 5W-30

PRODUCT CODE: 1635

APPLICATION

SELENIA WR Forward 5W-30 has been specifically designed to help prolong the life and maintain the efficiency of emission systems in diesel passenger car vehicles.

SELENIA WR Forward 5W-30 is particularly suitable for diesel engines equipped with particulate filters for manufacturers such as Renault.

SPECIFICATIONS

SAE 5W-30, ACEA C4, FIAT 9.55535-S4, RENAULT RN0720

TEST DESCRIPTION

| TEST DESCRIPTION | METHOD | UNIT | TYPICAL VALUE |
|-----------------------|-------------|-------------------|---------------|
| APPEARANCE | -- | -- | C & B |
| DENSITY AT 15°C | ASTM D4052 | g/cm ³ | 0.852 |
| VISCOSITY AT 100°C | ASTM D445 | cSt | 12 |
| VISCOSITY INDEX | ASTM D2270 | -- | 167 |
| VISCOSITY @ -30°C | ASTM D 5293 | cPs | 6300 |
| FLASH POINT CI. O. C. | ASTM D92 | °C | >200 |
| Pour point | ASTM D97 | °C | <-40 |
| FOAM AT 24°C | ASTM D892 | cc/s | 0 / 0 |
| T.B.N. | ASTM D2896 | mg KOH/g | >8 |

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

06/2015